

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/020458 A1

(51) International Patent Classification⁷: **H04B 1/707**

(21) International Application Number:
PCT/EP2004/007626

(22) International Filing Date: 10 July 2004 (10.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03388056.8 26 August 2003 (26.08.2003) EP
60/500,413 5 September 2003 (05.09.2003) US

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET L M ERICSSON (publ)** [SE/SE]; S-164 35 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JONSSON, Elias** [SE/SE]; Södra Promenaden 3, S-211 29 Malmö (SE).
PERSSON, Roger [SE/SE]; Lilla Kvarngatan 2A, S-211 29 Malmö (SE).

(74) Agent: **ZACCO DENMARK A/S**; Hans Bekkevolds Allé 7, DK-2900 Hellerup (DK).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: POSITIONING OF A PATH SEARCHER WINDOW IN A CDMA RECEIVER



(57) Abstract: Multipath components of signals transmitted through time-varying digital radio channels are received with individual delays, and signals through a given channel comprise a code identifying that channel. A delay profile indicating a magnitude (Y) for delay values in a search window is calculated repetitively for known channels; the delays of multipath components for known channels estimated; a signal strength indicator calculated; and a search for new multipath components not already estimated performed at regular time intervals. When a new multipath component is found, its identification code is compared to the codes of the known channels. If the code of the new component is identical to the code of a known channel, a delay profile and a signal strength indicator is calculated for a window transposed to include the new multipath component. In this way as many multipath components as possible are included in the search window for a new cell.

WO 2005/020458 A1